

GLOBAL  *base*

1 - CIRCUIT LIGHTING TRACK SYSTEM



**GBT 67**  
trafo-adapter

**NQA**

# GBT 67 trafo-adapter

FOR LOW VOLTAGE SPOTLIGHTS



GLOBAL trac®  
is registered trade mark of  
Nordic Aluminium Plc

We reserve the right to changes.



## COLOURS

- \* Grey-1
- \* Black-2
- \* White-3



## FEATURES OF THE ADAPTER

- \* Pull strength 100N
- \* Bending moment 2.5Nm
- \* Protection class II
- \* Nominal values: 75W  
prim 230V, 0.33A, 50/60Hz  
(UK prim 240V, 0.31A, 50/60Hz)  
sec 12V, 6.25A
- \* Dimmable
- \* Thermal and short circuit protection autoreset

## USE

Intended for the connection of 12V low voltage halogen spotlights to the GLOBAL base 1-circuit tracks. The GBT 67 trafo-adapter suits also Concord Lytespan 1 and Lytespan LP tracks.

## ALUMINIUM NIPPLES



XTSA 55/12  
M 13x1, l=12 mm  
rotating



XTSA 56/8  
M 13x1, l=8 mm  
fixed



XTSA 57/8  
M 10x1, l=8 mm  
rotating



XTSA 57/12  
M 10x1, l=12 mm  
rotating



XTSA 58/8  
M 10x1, l=8 mm  
fixed



**NORDIC  ALUMINIUM**

---

PO.Box 117, FIN-02401 Kirkkonummi, Finland

---

Tel. +358 9 68 251, fax +358 9 298 2154

---

[firstname.lastname@nordicaluminium.fi](mailto:firstname.lastname@nordicaluminium.fi)

---

[globalinfo@nordicaluminium.fi](mailto:globalinfo@nordicaluminium.fi)

---

[www.nordicaluminium.fi](http://www.nordicaluminium.fi)